

PWR

CAN 1

CAN2

KVASER USBCAN PRO 2XHS V2

Deet

USBcan Pro

EAN 73-30130-00752-9

CAN HS

The USBcan Pro 2xHS v2 is a USB to dual-channel CAN or CAN FD interface with scripting capability. With a standard USBconnector and two high-speed CAN channels with ISO 11898-2 compliant CAN transceivers in two separate 9-pin D-SUB CAN connectors, it is high-performance, yet compact, and can be used as a simple dual-channel interface to connect two high speed CAN buses to a PC or mobile computer, or can be programmed to do more. The Pro version is shipped with Kvaser TRX, a lightweight development environment that lowers the bar when starting out programming the device.



KVASER USBCAN PRO 2XHS V2

EAN 73-30130-00752-9

Major Features

- Supports CAN FD.
- Quick and easy plug-and-play installation.
- Supports both 11-bit (CAN 2.0A) and 29-bit (CAN 2.0B active) identifiers.
- Power is taken from the USB bus.
- Galvanic isolation.
- High-speed CAN connection (compliant with ISO 11898-2), up to 1 Mbit/s.
- Fully compatible with J1939, CANopen, NMEA 2000 and DeviceNet.
- Kvaser MagiSync provides automatic time synchronization between several PCto-bus interfaces connected to thesame PC.
- Programming functionality to support interface mode e.g. optimize protocol handling, pre-filter CAN messages directly on the interface or simulate missing hardware.
- Simultaneous operation of multiple devices.



Technical Data

Bitrate	50-1000 kbps
	-40 - 85 °C
Temp Range	
Timestamp	1
Messages Per Second Receive	20000 mps
Messages Per Second Sending	20000 mps
Weight	150 g
Length	170 mm
Height	25 mm
Channels	2
Certificates	CE, RoHS
Interfaces	USB
Categories	PC Interfaces, Interfaces
OS	Windows 10, 8, 7, Vista, XP, and Linux
Connectors	DSUB 9
Buffers	On Board Buffer
Galvanic Isolation	Yes
Error Frame Generation	Yes
Error Counters Reading	Yes
Silent Mode	Yes
Material	PA66
Sound	No
Current Consumption	max 500mA

WARRANTY

2-Year Warranty. See our General Conditions and Policies for details.

SUPPORT

Free Technical Support on all products available by contacting <u>info@gmga.vn</u>

SOFTWARE

Documentation, software and driverscan be downloaded for free, please <u>contact</u> <u>us!</u>

Units are shipped with Kvaser TRX, a lightweight development environment.

Kvaser CANlib SDK is a free resource that includes everything you need to develop software for the Kvaser CAN interfaces. Includes full documentation and many program samples, written inC, C++, C#, Delphi and Visual Basic.

All Kvaser CAN interface boards share a common software API. Programs writtenfor one interface type will run without modifications on the other interface types!

J2534 Application ProgrammingInterface available.

RP1210A Application Programming Interface available.

Online documentation in Windows HTML-Help and Adobe Acrobat format.