## List of changes made to Larson Davis Spartan 721-821

# Spartan 721-821 Version 1.300

#### Features

- 1. Measurement History Added whole/third octave data to Measurement History interval data.
- 2. Calibration Precision Consistency Two decimal places of precision are now shown for calibration levels, deltas, and sensitivity.
- 3. Custom Report Settings Added firmware support for custom report settings saved with meter data files.
- 4. Support for Finnish Added firmware support for Finnish (Suomi).

# **Spartan 721-821 Version 1.201**

Fixed

1. Full OBA Value Labels show selected frequency bin – In the UI, opening either Live or Overall with OBA set to 1/1, the data labels would show the summation character ( $\Sigma$ ) instead of the selected frequency. Selecting a frequency would correct it but leaving and returning to the tab would result in it showing the summation character again. The value being shown was correct for the selected frequency on the graph.

# Spartan 721-821 Version 1.200

### 821IH-QPR Support

- 1. Added support for the 377A12 1/4" pressure, pre-polarized condenser microphone.
- 2. The meter will dynamically adjust the range of the Ln table according to the sensitivity of the selected microphone.
- 3. User entered settings for "Other" microphone are now retained when switching to a standard mic and back.

### Measurement History

4. Added a 3-minute measurement interval option as well as a manual option.

# Spartan 721-821 Version 1.110

### **Time History**

1. Fixed issue where Time History data could become delayed if the meter was reset while running. This caused old data to be added to the beginning of the next Time History file, shifting the current histories to later in the file. This could be avoided by stopping the measurement before resetting the meter.

#### Spartan 721-821 Version 1.101 **Format SD card**

# December 2023

**March 2024** 

# **April 2024**

**April 2024** 

## June 2024



# LARSON DAVIS

 Fixed issue where the format SD card feature would only partially format the card. This sometimes caused corrupt files and file lists. This issue was introduced in version 1.100. Upgrading to 1.101 or later and using the format SD card function will repair any corrupt SD cards.

#### Spartan 721-821 Version 1.100

#### December 2023

#### **Measurement History Ln Percentiles**

1. Added Ln Percentiles to Measurement History.

#### **Extended Valid Ln Percentile Range**

2. Extended Ln Percentile range settings from 0.1%-99.9% to 0.0%-100.0%.

#### Meter User Interface

- 3. Added German to supported languages, and updated missing/mistranslated French and Italian text.
- 4. Added Set Date & Time functionality to System Utilities on meter. This allows the time to be set manually on the device. Previously this could only be set with G4.
- 5. Improved the layout of navigation controls on the Time History tab to be more convenient.
- 6. Added measurement history period, run time, and pause time to the Measurement History Bar Graph that remains at the top of the tab.
- 7. Improved navigation responsiveness on the Time History and Measurement History tabs. This also improved time history and measurement history view responsiveness within G4.
- 8. Improved the clarity of the OBA legends to include frequency for the selected band in metric name. Previously, the meter only displayed the frequency in the bar graph and not the legend.
- 9. Fixed the Measurement Metrics card on Measurement History tab which showed incorrect Leq values because they used pause time in their calculations. This caused any displayed Leq values to drift down while the measurement was paused. Now only the actual run time is used. The meter calculated the stored data correctly. This did not affect the stored data nor the Measurement Any Data card.
- 10. Fixed an error where time history data could be missing from the time history graph. This data could only be viewed once the file was stored. This was intermittent and more common with large amounts of data.
- 11. Dosimetry and Ln cards now correctly follow the decimal preference setting. Previously, a period was always displayed for the decimal separator.
- 12. Files could be corrupted and generate parse errors when being opened by G4 if Markers contained invalid characters. The meter now prevents invalid characters from being entered. Valid characters are letters, numbers, and '#'.

#### External Disconnect Voltage Default

Default value for external disconnect setting changed from 10.8 V to 10.5 V. This accounts for a 300 mV drop offset that exists with the displayed external voltage compared to measured external voltage at the connector.

#### Weighting Filter Adjustments

14. Minor adjustments to A and C Weight filter coefficients to better match nominal filter shape at frequencies higher than 4 kHz. The filter shapes before were within specifications for A and C weight filters, but these improvements match the nominal shape better for high frequencies.

#### Time History with 100ms Period

15. Fixed an issue where Time history data could be stored incorrectly when running at the 100 MS time history rate.

#### Spartan 721-821 Version 1.002

1. The decreased run time, increased power consumption, created in 1.001 has been rectified.

#### Spartan 721-821 Version 1.001

- 1. Fixed issue where the meter would lock up when entering sleep mode.
- 2. When entering sleep mode, without OBA enabled, data could become corrupted.

#### Spartan 721-821 Version 1.000

1. Initial Release

GMGA MEASURING Address: No. 33 Alley 99/120 Dinh Cong Ha, Dinh Cong Ward, Hoang Mai District, 10000 Hanoi City, Vietnam Telephone: <u>+84 845 969 336</u> Email: <u>info@gmga.vn</u> Website: <u>https://gmga.vn/</u>

June 2023



June 2023

**July 2023**